



Becker County Planning & Zoning
915 Lake Ave
Detroit Lakes, MN 56501
(218) 846-7314
www.co.becker.mn.us

140148000-2024

Certificate of Compliance
Inspection Report - Permit #: SS2024-2138



Owner & Property Information

Owner Name:	DOUGLAS K & LAURI ASKELSON	Site Address:	17170 220TH ST
Mailing Address:	DOUGLAS K & LAURI ASKELSON 17170 220TH ST AUDUBON MN 56511	Township - Sec/Twp/Rng:	HAMDEN - 31/140/042
Parcel #:	140148000	Legal Description:	S1/2 OF SW1/4
Secondary Parcel #:		Designer:	Crescent Septic Services LLC L4224 (Peter Johnson)
		Installer:	Boit Excavating, L559 (Todd Boit)

Inspector Verified Specifications

Insp- Effluent Screen Installed:	No	Insp- Tank Nbr/Size:	0/1000/500
Insp- Alarm Required:	Yes	Insp- Drainfield Type:	Mound
Insp- Lift Pump in System:	Yes	Insp- Drainfield Size:	10X38 ROCK BED
Insp- Number of Bedrooms:	3	Insp- Soil Verification:	#1:see attached #2:N/A #3:N/A

Inspector Verified Setbacks

Insp- Tank Dist to Road	EXISTING	Insp- Drainfield Dist to Road	10+
Insp- Tank Dist to Nearest Prop Line	EXISTING	Insp- Drainfield Dist to Nearest Prop Line	10+
Insp- Tank Dist to Nearest Structure	EXISTING	Insp- Drainfield Dist to Nearest Structure	20+
Insp- Tank Dist to Well	EXISTING	Insp- Drainfield Dist to Well	50+
Insp- Tank Dist to OHW	EXISTING	Insp- Drainfield Dist to OHW	150+
Insp- Tank Dist to Pond/Wetland	EXISTING	Insp- Drainfield Dist to Pond/Wetland	50
Insp- Tank Dist to Pressure Line	EXISTING	Insp- Drainfield Dist to Pressure Line	NA

Certificate of Compliance

(Yes) Certificate is hereby granted based upon the application, addendum from, plans, specifications and all other supporting data. With proper maintenance, this system can be expected to function satisfactory, however this is not a guarantee.

Certification Date: 09/04/2024

Zoning Office Signature:

Jeff Rusness - ISTS Inspector

* Certificate of Compliance is not valid unless signed by a Registered Qualified Employee *

Field Review Form

Permit # SS2024-2138

Property and Owner

Owner: DOUGLAS K & LAURI ASKELSON

Parcel Number: 140148000

Site Address: 17170 220TH ST

Secondary Parcel:

Home Information

Does the structure contain any of the following elements?	Designer submitted	Inspector verified
	Garbage disposal: No Dishwasher: Grinder pump: Lift pump in bsmt:	Garbage disposal? <input checked="" type="checkbox"/> N Dishwasher? <input checked="" type="checkbox"/> Y Grinder pump? <input checked="" type="checkbox"/> N Lift pump in basement? <input checked="" type="checkbox"/> Y N
Number of bedrooms: 3	Review - Number of bedrooms: 3	
Effluent screen	Effluent screen installed? <input checked="" type="checkbox"/> Y N	Mfr:
Alarm: No Type: unknown	Review - Alarm? Y N	Type & Mfr: Existing
Lift pump in system: Yes	Review - Lift pump in system? Y N	Mfr: Existing

Component Information

Tank size: 1000/500	Review - Tank nbr: size: Existing
Drainfield type: Mound	Review - Drainfield type: Mound
Drainfield size: Full size - 380 Reduced/warr. size -	Review - Drainfield status: none / installed / next spring Review - Drainfield size: 10 x 58 Rock Bed
Absorption area size: 9"	Review - Absorption area size:
Chamber type/num: Trench sqft/chamber -	Review - Chamber type: Review - Trench sqft/chamber: N/A
Drainfield rock depth: 9"	Review - Rock depth: 9 in

Soil Verification

Vertical separation verified <i>See attached.</i>	Boring #1: Boring #2: Boring #3:
--	--

Setback Verification

Distance to...	Designer submitted		Inspector verified	
	Tank	Drainfield	Tank	Drainfield
Road	166	182	Existing	10
Nearest prop line	860	830		10
Nearest structure	53	78		20
Well	178	190		50
OHW	563	533		150
Pond/Wetland				50
Pressure line	90	135		N/A

Date System Installed: 6-30-2024 Installer: Boitell

Inspector: *Paul Turner*



Preliminary Evaluation Worksheet



1. Contact Information

v 03.15.2023

Property Owner/Client:	Doug and Lauri Askelson	Date Completed:	8/16/2024	
Site Address:	17170 220th St Audubon, MN 56511	Project ID:		
Email:		Phone:	701-200-6082	
Mailing Address:	26838 COUNTY HIGHWAY 1	Alt Phone:		
Legal Description:	S1/2 OF SW1/4			
Parcel ID:	140148000	SEC:	31	
	TWP:	140	RNG:	042

2. Flow and General System Information

A. Client-Provided Information

Project Type: New Construction Replacement Expansion Repair

Project Use: Residential Other Establishment:

Residential use: # Bedrooms: Dwelling sq.ft.: Unfinished sq.ft.:

Adults: # Children: # Teenagers:

In-home business (Y/N): If yes, describe:

<input type="checkbox"/> Garbage Disposal/Grinder	<input type="checkbox"/> Dishwasher	<input type="checkbox"/> Hot Tub*
<input type="checkbox"/> Sewage pump in basement	<input type="checkbox"/> Water Softener*	<input type="checkbox"/> Sump Pump*
<input type="checkbox"/> Large Bathtub >40 gallons	<input type="checkbox"/> Iron Filter*	<input type="checkbox"/> Self-Cleaning Humidifier*
<input type="checkbox"/> Clothes Washing Machine	<input type="checkbox"/> High Eff. Furnace*	<input type="checkbox"/> Other: <input type="text"/>

* Clear water source - should not go into system

Additional current or future uses:

Anticipated non-domestic waste:

The above is complete & accurate:

Client signature & date

B. Designer-determined Flow and Anticipated Waste Strength Information

Attach additional information as necessary.

Design Flow: GPD Anticipated Waste Type: Residential

Maximum Concentration BOD: mg/L TSS: mg/L Oil & Grease: mg/L

3. Preliminary Site Information

A. Water Supply Wells

#	Description	Mn. ID#	Well Depth (ft.)	Casing Depth (ft.)	Confining Layer	STA Setback	Source
1	Deep Well	825878	81	77	unk	50	MDH
2							
3							
4							

Additional Well Information:

Preliminary Evaluation Worksheet

Site within 200' of noncommunity transient well (Y/N)	<input type="checkbox"/> No	Yes, source: _____
Site within a drinking water supply management area (Y/N)	<input type="checkbox"/> No	Yes, source: _____
Site in Well Head Protection inner wellhead management zone (Y/N)	<input type="checkbox"/> No	Yes, source: _____
Buried water supply pipes within 50 ft of proposed system (Y/N)	<input type="checkbox"/> No	
B. Site located in a shoreland district/area?		
Elevation of ordinary high water level:	<input type="checkbox"/> N/A ft	Source: _____ N/A
Classification:	<input type="checkbox"/> N/A	Tank Setback: <input type="checkbox"/> N/A ft. STA Setback: <input type="checkbox"/> N/A ft.
C. Site located in a floodplain?		
Floodplain designation/elevation (10 Year):	<input type="checkbox"/> N/A ft	Yes, Type(s): _____ N/A
Floodplain designation/elevation (100 Year):	<input type="checkbox"/> N/A ft	Source: _____ N/A
D. Property Line Id / Source: <input type="checkbox"/> Owner <input type="checkbox"/> Survey <input checked="" type="checkbox"/> County GIS <input type="checkbox"/> Plat Map <input type="checkbox"/> Other: _____		
E. ID distance of relevant setbacks on map: <input type="checkbox"/> Water <input type="checkbox"/> Easements <input checked="" type="checkbox"/> Well(s) <input checked="" type="checkbox"/> Building(s) <input checked="" type="checkbox"/> Property Lines <input type="checkbox"/> OHWL <input type="checkbox"/> Other: _____		

4. Preliminary Soil Profile Information From Web Soil Survey (attach map & description)

Map Units:	<input type="checkbox"/> J119D	Slope Range: <input type="checkbox"/> 3-15 %
List landforms:	<input type="checkbox"/> Ground moraines	
Landform position(s):	<input type="checkbox"/> Back/ Side Slope	
Parent materials:	<input type="checkbox"/> Till	
Depth to Bedrock/Restrictive Feature:	<input type="checkbox"/> >80 in	Depth to Watertable: <input type="checkbox"/> 59-75 in
Map Unit Ratings	Septic Tank Absorption Field- At-grade:	<input type="checkbox"/> Extremely Limited
	Septic Tank Absorption Field- Mound:	<input type="checkbox"/> Extremely Limited
	Septic Tank Absorption Field- Trench:	<input type="checkbox"/> Moderately Limited

5. Local Government Unit Information

Name of LGU:	<input type="checkbox"/> Becker County Planning and Zoning	
LGU Contact:	<input type="checkbox"/> Kyle Vareberg	
LGU-specific setbacks:	<input type="checkbox"/>	
LGU-specific design requirements:	<input type="checkbox"/>	
LGU-specific installation requirements:	<input type="checkbox"/>	
Notes:	<input type="checkbox"/>	

Field
Evaluation Worksheet

1. Project Information

v 03.15.2023

Property Owner/Client:

Project ID:

Site Address:

Date Completed:

2. Utility and Structure Information

Utility Locations Identified Gopher State One Call # Any Private Utilities:

Locate and Verify (see Site Evaluation map) Existing Buildings Improvements Easements Setbacks

3. Site Information

Vegetation type(s): Landscape position:

Percent slope: % Slope shape: Slope direction:

Describe the flooding or run-on potential of site:

Describe the need for Type III or Type IV system:

Note:

Proposed soil treatment area protected? (Y/N): If yes, describe:

4. General Soils Information

Filled, Compacted, Disturbed areas (Y/N):

If yes, describe:

Soil observations were conducted in the proposed system location (Y/N):

A soil observation in the most limiting area of the proposed system (Y/N):

Number of soil observations: Soil observation logs attached (Y/N):

Percolation tests performed & attached (Y/N):

5. Phase I. Reporting Information

Limiting Condition*	Depth	Elevation	
Periodically saturated soil:	28 in	95.1 ft	*Most Restrictive Depth Identified from List Below
Standing water:	28 in	95.1 ft	Soil Texture: <input type="text" value="Clay Loam"/>
Bedrock:	in	ft	Percolation Rate: <input type="text"/> min/inch
Benchmark Elevation:	100.0 ft	Elevations and Benchmark on map? (Y/N):	<input type="text" value="Yes"/> Soil Hyd Loading Rate: <input type="text" value="0.45"/> gpd/sq.ft

Benchmark Elevation Location:

Differences between soil survey and field evaluation:

Site evaluation issues / comments:

Anticipated construction issues:

Soil Observation Log

Project ID: v 03.15.2023

Client:	Doug and Lauri Askelson											
Soil parent material(s): (Check all that apply)												
Landscape Position:		Back/Side Slope	Slope %:	10.0	Slope shape:	Linear, Linear		Alluvium <input type="checkbox"/> Bedrock <input type="checkbox"/> Organic Matter			Flooding/Run-On potential: <input type="checkbox"/> Disturbed/Fill	
Vegetation:	Forest		Soil survey map units:		J119D		Surface Elevation-Relative to benchmark:			98.4		
Date/Time of Day/Weather Conditions:			8/19/2024		noon		Limiting Layer Elevation:			95.2		
Observation #/Location:		1		NE Corner of STA		Observation Type:		I----- Structure-----I				
Depth (in)	Texture	Rock Frag. %	Matrix Color(s)	Mottle Color(s)	Redox Kind(s)	Indicator(s)	Shape	Grade	Consistence			
0-13	Medium Sandy Loam	0	10YR 2/2				Blocky	Moderate	Friable			
13-22	Clay Loam	0	10YR 3/2				Blocky	Moderate	Friable			
22-28	Clay Loam	0	10YR 3/3				Blocky	Moderate	Friable			
28-38	Clay Loam	0	10YR 5/4	10YR 6/4			Blocky	Moderate	Friable			
38	Clay Loam	0	10YR 5/4	10YR 6/2	Depletions		Blocky	Moderate	Friable			
			10YR 3/2	10YR 6/4								
					10YR 5/6	Concentrations						
					10YR 7/3							
Comments: 38" numerous colors												
I hereby certify that I have completed this work in accordance with all applicable ordinances, rules and laws.												
Peter Johnson		Peter Johnson		L4224		8/19/2024						
(Designer/Inspector)		(Signature)		(License #)		(Date)						
Optional Verification: I hereby certify that this soil observation was verified according to Minn. R. 7082.0500 subp. 3 A. The signature below represents an infiel verification of the periodically saturated soil or bedrock at the proposed soil treatment and dispersal site.												
(LGU/Designer/Inspector)		(Signature)		(Cert #)								
(Date)												



1. PROJECT INFORMATION

v 03.15.2023

Property Owner/Client: Project ID:
 Site Address: Date:
 Email Address:
 Phone:

2. DESIGN FLOW & WASTE STRENGTH

Attach waste strength data/estimated strength for Other Establishments

Design Flow: GPD Anticipated Waste Type:
 BOD: mg/L TSS: mg/L Oil & Grease: mg/L
 Treatment Level: *Select Treatment Level C for residential septic tank effluent*

3. HOLDING TANK SIZING

Minimum Capacity: Residential = 1000 gal or 400 gal/bedroom, Other Establishment = Design Flow x 5.0, Minimum size 1000 gallons

Code Minimum Holding Tank Capacity: Gallons with Tanks or Compartments

Recommended Holding Tank Capacity: Gallons with Tanks or Compartments

Type of High Level Alarm: (Set @ 75% tank capacity)

Comments:

4. SEPTIC TANK SIZING

A. Residential dwellings:

Number of Bedrooms (Residential):

Code Minimum Septic Tank Capacity: Gallons with Tanks or Compartments

Recommended Septic Tank Capacity: Gallons with Tanks or Compartments

Effluent Screen & Alarm (Y/N): Model/Type:

B. Other Establishments:

Waste received by: GPD x Days Hyd. Retention Time

Code Minimum Septic Tank Capacity: Gallons with Tanks or Compartments

Recommended Septic Tank Capacity: Gallons with Tanks or Compartments

Effluent Screen & Alarm (Y/N): Model/Type:

* Other Establishments Require Department of Labor and Industry Approval and Inspection for Building Sewer *

5. PUMP TANK SIZING

Soil Treatment Dosing Tank

Pump Tank Capacity (Minimum): Gal

Pump Tank Capacity (Recommended): Gal

Pump Req: GPM Total Head ft

Supply Pipe Dia. in Dose Vol: gal

Other Component Dosing Tank:

Pump Tank Capacity (Minimum): Gal

Pump Tank Capacity (Recommended): Gal

Pump Req: GPM Total Head ft

Supply Pipe Dia. in Dose Vol: Gal

* Flow measurement device must be incorporated for any system with a pump: Elapsed Time Meter and/or Event Counter *

6. SYSTEM AND DISTRIBUTION TYPE

Project ID:

Soil Treatment Type:	Mound	Distribution Type:	Pressure Distribution-Level	
Elevation Benchmark:	100.0	ft	Benchmark Location:	nail in tree, center of east side of
MPCA System Type:	Type I	Distribution Media:	Rock	
Type III/IV/V Details:	n/a			

7. SITE EVALUATION SUMMARY:

Describe Limiting Condition: Redoximorphic Features/Saturated Soils

Layers with >35% Rock Fragments? (yes/no) No If yes, describe below: % rock and layer thickness, amount of soil credit and any additional information for addressing the rock fragments in this design.

Note:

Limiting Condition:	Depth	Depth	Elevation of Limiting Condition
28	inches	2.3	ft 95.10 ft <i>Critical for system compliance</i>
Minimum Req'd Separation:	36	inches	3.0 ft <i>Distribution Elevation > Code Max Depth</i>
Code Max System Depth*:	Mound	inches	-0.7 ft 98.10 ft Elevation OK

*This is the maximum depth to the bottom of the distribution media for required separation. Negative Depth (ft) requires a mound.

Designed Distribution Elevation: 98.4 ft Minimum Sand Depth: 12.0 inches

A. Soil Texture:	Clay Loam	B. Organic Loading Rate (optional):	<input type="text"/> lbs/sq.ft/day 0
C. Soil Hyd. Loading Rate:	0.45	GPD/ft ²	D: Percolation Rate: <input type="text"/> MPI
E. Contour Loading Rate:	11.8	Note:	<input type="text"/>
F. Measured Land Slope:	10.0	%	Note: <input type="text"/>
Comments: <input type="text"/>			

8. SOIL TREATMENT AREA DESIGN SUMMARY

Trench:

Dispersal Area	<input type="text"/> sq.ft	Sidewall Depth	<input type="text"/> in	Trench Width	<input type="text"/> ft
Total Lineal Feet	<input type="text"/> ft	No. of Trenches	<input type="text"/>	Code Max. Trench Depth	<input type="text"/> in
Contour Loading Rate	<input type="text"/> ft	Minimum Length	<input type="text"/> ft	Designed Trench Depth	<input type="text"/> in

Bed:

Dispersal Area	<input type="text"/> sq.ft	Sidewall Depth	<input type="text"/> in	Maximum Bed Depth	<input type="text"/> in
Bed Width	<input type="text"/> ft	Bed Length	<input type="text"/> ft	Designed Bed Depth	<input type="text"/> in

Mound:

Dispersal Area	380.0	sq.ft	Bed Length	38.0	ft	Bed Width	10.0	ft
Absorption Width	26.0	ft	Clean Sand Lift	1.0	ft	Berm Width (0-1%)	<input type="text"/>	ft
Upslope Berm Width	8.7	ft	Downslope Berm	27.0	ft	Endslope Berm Width	16.2	ft
Total System Length	70.4	ft	System Width	45.7	ft	Contour Loading Rate	12.0	gal/ft

Project ID:

At-Grade:

Dispersal Area	<input type="text"/>	sq.ft	Bed Length	<input type="text"/>	ft	Bed Width	<input type="text"/>	ft
Upslope Berm	<input type="text"/>	ft	Downslope Berm	<input type="text"/>	ft	Finished Height	<input type="text"/>	ft
System Length	<input type="text"/>	ft	Endslope Berm	<input type="text"/>	ft	System Width	<input type="text"/>	ft

Level & Equal Pressure Distribution Soil Treatment Area

No. of Laterals	<input type="text"/> 3	Lateral Diameter	<input type="text"/> 1.50	in	Lateral Spacing	<input type="text"/> 3	ft	
Perforation Spacing	<input type="text"/> 3	ft	Perforation Diameter	<input type="text"/> 1/4	in	Drainback Volume	<input type="text"/> 5	gal
Min Dose Volume	<input type="text"/> 48	gal	Max Dose Volume	<input type="text"/> 113	gal	Total Dosing Volume	<input type="text"/> 85	gal

Non-Level and Unequal Pressure Distribution Soil Treatment Area

	Elevation (ft)	Pipe Size (in)	Pipe Volume (gal/ft)	Pipe Length (ft)	Perf Size (in)	Spacing (ft)	Spacing (in)	Minimum Dose Volume <input type="text"/> gal
Lateral 1								
Lateral 2								
Lateral 3								
Lateral 4								
Lateral 5								
Lateral 6								

9. Organic Loading and Additional Info for At-Risk, HSW or Type IV Design

Organic Loading to Soil Treatment

A. Starting BOD Concentration = Design Flow X 0.7 X Starting BOD (mg/L) X 8.35 ÷ 1,000,000

gpd X mg/L X 8.35 ÷ 1,000,000 = lbs. BOD/day (Organic Loading Design)

B. Organic Loading to Soil Treatment Area: (enter loading value in 7B)

mg/L X gpd X 0.7 X 8.35 ÷ 1,000,000 ÷ sq.ft = lbs./day/sqft

HSW Technology Strength Reduction

A. Starting BOD Concentration = Design Flow X Starting BOD (mg/L) X 8.35 ÷ 1,000,000

gpd X mg/L X 8.35 ÷ 1,000,000 = lbs. BOD/day (HSW Technology Design)

B. Target BOD Concentration = Design Flow X Target BOD (mg/L) X 8.35 ÷ 1,000,000

gpd X mg/L X 8.35 ÷ 1,000,000 = lbs. BOD/day (HSW Technology Design)

Lbs. BOD To Be Removed: lbs. BOD/day (HSW Technology Design)

Pretreatment Technology: *Must Meet or Exceed Target

Disinfection Technology: *Required for Levels A & B

10. Comments/Special Design Considerations:

I hereby certify that I have completed this work in accordance with all applicable ordinances, rules and laws.

Peter Johnson

(Designer)

Peter Johnson

(Signature)

L4224

8/21/2024

(Date)



Mound Design Worksheet ≥1% Slope



1. SYSTEM SIZING:

Project ID:

v 03.15.2023

A. Design Flow:	450	GPD
B. Soil Loading Rate:	0.45	GPD/sqft
C. Depth to Limiting Condition	2.3	ft
D. Percent Land Slope:	10.0	%
E. Media (Sand) Loading Rate:	1.2	GPD/sqft
F. Mound Absorption Ratio:	2.60	

TABLE IXa

LOADING RATES FOR DETERMINING BOTTOM ABSORPTION AREA AND ABSORPTION RATIOS USING PERCOLATION TESTS

Percolation Rate (MPI)	Treatment Level C		Treatment Level A, A-2, B, B-2	
	Absorption Area Loading Rate (gpd/ft ²)	Mound Absorption Ratio	Absorption Area Loading Rate (gpd/ft ²)	Mound Absorption Ratio
<0.1	-	1	-	1
0.1 to 5	1.2	1	1.6	1
0.1 to 5 (fine sand and loamy fine sand)	0.6	2	1	1.6
6 to 15	0.78	1.5	1	1.6
16 to 30	0.6	2	0.78	2
31 to 45	0.5	2.4	0.78	2
46 to 60	0.45	2.6	0.6	2.6
61 to 120	-	5	0.3	5.3
>120	-	-	-	-

Table I
MOUND CONTOUR LOADING RATES:

Measured Perc Rate	← OR →	Texture - derived mound absorption ratio	Contour Loading Rate:
≤ 60mpi	← OR →	1.0, 1.3, 2.0, 2.4, 2.6	→ ≤12
61-120 mpi	← OR →	5.0	→ ≤12
≥ 120 mpi*		>5.0*	→ ≤6*

*Systems with these values are not Type I systems.
Contour Loading Rate (linear loading rate) is a recommended value.

2. DISPERSAL MEDIA SIZING

A. Hydraulic Absorption Required Bottom Area: Design Flow (1A) ÷ Design Media Loading Rate(1E)

$$450 \text{ GPD} \div 1.2 \text{ GPD/sqft} = 375 \text{ sq.ft}$$

Organic Sizing (OPTIONAL)

B. Organic Absorption Bed Area = Organic Loading (Summary 9A) ÷ Organic Soil Loading Rate (Summary 7B)

$$\text{[] lbs BOD} \div \text{[] lbs BOD/sq.ft} = \text{[] sq.ft}$$

C. Required Bed Area = Greater of Hydraulic (1D) or Organic Bed Area (1E) 375 sq.ft

D. Designed Dispersal Media Area: 380 sq.ft Optional upsizing of area to be larger than 2C

B. Enter Dispersal Bed Width: 10.0 ft Can not exceed 10 feet

C. Calculate Contour Loading Rate: Bed Width(2B) X Design Media Loading Rate(1E)

$$10 \text{ ft} \times 1.2 \text{ GPD/sqft} = 12.0 \text{ gal/ft} \quad \text{Can not exceed Table 1}$$

D. Calculate Minimum Dispersal Bed Length: Dispersal Bed Area(2A) ÷ Bed Width(2B)

$$380 \text{ sqft} \div 10.0 \text{ ft} = 38.0 \text{ ft}$$

If a larger dispersal media Length is desired, enter size: 38 ft

3. ABSORPTION AREA SIZING

A. Calculate Absorption Width: Bed Width(2B) X Mound Absorption Ratio(1F)

$$10.0 \text{ ft} \times 2.6 = 26.0 \text{ ft}$$

B. For slopes >1%, the Absorption Width is measured downhill from the upslope edge of the Bed.

Calculate Downslope Absorption Width: Absorption Width(1F) - Bed Width(2B)

$$26.0 \text{ ft} - 10.0 \text{ ft} = 16.0 \text{ ft}$$

4. DISTRIBUTION MEDIA:

Project ID:

Select Dispersal Media:

Rock

Enter Either 4A or 4B

A. Rock Depth Below Distribution Pipe

9 in

B. Registered Media

Check registered product
information for specific
application details and design

Registered Media Depth

in

Specific Media Comments:

5. MOUND SIZING

Project ID:

A. Clean Sand Lift: Required Separation - Depth to Limiting Condition = Clean Sand Lift (1 ft minimum)

$$3.0 \text{ ft} - 2.3 \text{ ft} = 1.0 \text{ ft} \quad \text{Design Sand Lift (optional): } 1 \text{ ft}$$

B. Upslope Height: Clean Sand Lift(6A) + Depth of Media(4AorB) +Depth to Cover Pipe+ Depth of Cover (1 ft)

$$1.0 \text{ ft} + 0.75 \text{ ft} + 0.3 \text{ ft} + 1.0 \text{ ft} = 3.1 \text{ ft}$$

Land Slope %	0	1	2	3	4	5	6	7	8	9	10	11	12
Upslope Berm Ratio	3:1	3.00	2.91	2.83	2.75	2.68	2.61	2.54	2.48	2.42	2.36	2.31	2.26
	4:1	4.00	3.85	3.70	3.57	3.45	3.33	3.23	3.12	3.03	2.94	2.86	2.78

C. Select Upslope Berm Multiplier (based on land slope):

2.86

D. Calculate Upslope Berm Width: Multiplier (5C) X Upslope Mound Height (5B)

$$2.86 \times 3.1 \text{ ft} = 8.7 \text{ ft}$$

E. Calculate Drop in Elevation Under Bed: Bed Width(2B) X Land Slope(1D) \div 100 = Drop (ft)

$$10.0 \text{ ft} \times 10.0 \% \div 100 = 1.00 \text{ ft}$$

F. Calculate Downslope Mound Height: Upslope Height(5B) + Drop in Elevation(5E)

$$3.1 \text{ ft} + 1.00 \text{ ft} = 4.1 \text{ ft}$$

Land Slope %	0	1	2	3	4	5	6	7	8	9	10	11	12
Downslope Ratio	3:1	3.00	3.09	3.19	3.30	3.41	3.53	3.66	3.80	3.95	4.11	4.29	4.48
	4:1	4.00	4.17	4.35	4.54	4.76	5.00	5.26	5.56	5.88	6.25	6.67	7.14

G. Select Downslope Berm Multiplier (based on land slope):

6.67

H. Calculate Downslope Berm Width: Downslope Multiplier(5G) X Downslope Height (5F)

$$6.67 \times 4.1 \text{ ft} = 27.0 \text{ ft}$$

I. Calculate Minimum Berm to Cover Absorption Area: Downslope Absorption Width(3A) + 4 feet

$$16.0 \text{ ft} + 4 \text{ ft} = 20.0 \text{ ft}$$

J. Design Downslope Berm = greater of 5H and 5I:

27.0 ft

K. Select Endslope Berm Multiplier:

4.00

(usually 3.0 or 4.0)

L. Calculate Endslope Berm Width = Endslope Berm Multiplier(5K) X Downslope Mound Height(5F)

$$4.00 \times 4.1 \text{ ft} = 16.2 \text{ ft}$$

M. Calculate Mound Width: Upslope Berm Width(5D) + Bed Width(2B) + Downslope Berm Width(5J)



$$8.7 \text{ ft} + 10.0 \text{ ft} + 27.0 \text{ ft} = 45.7 \text{ ft}$$

N. Calculate Mound Length: Endslope Berm Width (5L) + Bed Length(2D) + Endslope Berm Width(5L)

$$16.2 \text{ ft} + 38.0 \text{ ft} + 16.2 \text{ ft} = 70.4 \text{ ft}$$

6. MOUND DIMENSIONS (Feet)

Project ID:

Required Separation: (in)Elevation to Benchmark ftDistribution Media: Elevation required Separation: ftMedia Depth: (in)Elevation Distribution Media Bottom: ftManifold Connection: Elevation Top of Media(min): ftLateral Pipe Diameter: (in)Elevation Top of System(min): ftPerforation Size: (in)Perforation Spacing: (in)

If Split and Non-Level Pressure Distribution Used: See Non-Level Pressure Distribution Form

Comments:



Mound Materials Worksheet



Project ID:

v 03.15.2023

A. Rock Volume : (Rock Below Pipe + Rock to cover pipe (pipe outside dia + ~2 inch)) X Bed Length X Bed Width = Volume

$$(\boxed{9} \text{ in} + \boxed{3.0} \text{ in}) \div 12 \times \boxed{38.0} \text{ ft} \times \boxed{10.0} \text{ ft} = \boxed{380.0} \text{ cu.ft}$$

Divide cu.ft by 27 cu.ft/cu.yd to calculate cubic yards: $\boxed{380.0} \text{ cu.ft} \div 27 = \boxed{14.1} \text{ cu.yd}$

Add 30% for constructability: $\boxed{14.1} \text{ cu.yd} \times 1.3 = \boxed{18.3} \text{ cu.yd}$

B. Calculate Clean Sand Volume:

Volume Under Rock bed : Average Sand Depth x Media Width x Media Length = cubic feet

$$\boxed{1.5} \text{ ft} \times \boxed{10.0} \text{ ft} \times \boxed{38} \text{ ft} = \boxed{570} \text{ cu.ft}$$

For a Mound on a slope from 0-1%

Volume from Length = ((Upslope Mound Height - 1) X Absorption Width Beyond Bed X Media Bed Length)

$$(\boxed{\text{ft} - 1}) \times \boxed{\text{ft}} \times \boxed{\text{ft}} = \boxed{\text{ft}}$$

Volume from Width = ((Upslope Mound Height - 1) X Absorption Width Beyond Bed X Media Bed Width)

$$(\boxed{\text{ft} - 1}) \times \boxed{\text{ft}} \times \boxed{\text{ft}} = \boxed{\text{ft}}$$

Total Clean Sand Volume : Volume from Length + Volume from Width + Volume Under Media

$$\boxed{\text{cu.ft}} + \boxed{\text{cu.ft}} + \boxed{\text{cu.ft}} = \boxed{\text{cu.ft}}$$

For a Mound on a slope greater than 1%

Upslope Volume : ((Upslope Mound Height - 1) x 3 x Bed Length) ÷ 2 = cubic feet

$$((\boxed{3.1} \text{ ft} - 1) \times 3.0 \text{ ft} \times \boxed{38.0}) \div 2 = \boxed{116.9} \text{ cu.ft}$$

Downslope Volume : ((Downslope Height - 1) x Downslope Absorption Width x Media Length) ÷ 2 = cubic feet

$$((\boxed{4.1} \text{ ft} - 1) \times \boxed{16.0} \text{ ft} \times \boxed{38.0}) \div 2 = \boxed{927.2} \text{ cu.ft}$$

Endslope Volume : (Downslope Mound Height - 1) x 3 x Media Width = cubic feet

$$(\boxed{4.1} \text{ ft} - 1) \times 3.0 \text{ ft} \times \boxed{10.0} \text{ ft} = \boxed{91.5} \text{ cu.ft}$$

Total Clean Sand Volume : Upslope Volume + Downslope Volume + Endslope Volume + Volume Under Media

$$\boxed{116.9} \text{ cu.ft} + \boxed{927.2} \text{ cu.ft} + \boxed{91.5} \text{ cu.ft} + \boxed{570.0} \text{ cu.ft} = \boxed{1705.6} \text{ cu.ft}$$

Divide cu.ft by 27 cu.ft/cu.yd to calculate cubic yards: $\boxed{1705.6} \text{ cu.ft} \div 27 = \boxed{63.2} \text{ cu.yd}$

Add 30% for constructability: $\boxed{63.2} \text{ cu.yd} \times 1.3 = \boxed{82.1} \text{ cu.yd}$

C. Calculate Sandy Berm Volume:

Total Berm Volume (approx.) : ((Avg. Mound Height - 0.5 ft topsoil) x Mound Width x Mound Length) ÷ 2

$$((\boxed{3.6} - 0.5) \text{ ft} \times \boxed{45.7} \text{ ft} \times \boxed{70.4}) \div 2 = \boxed{4910.3} \text{ cu.ft}$$

Total Mound Volume - Clean Sand volume -Rock Volume = cubic feet

$$\boxed{4910.3} \text{ cu.ft} - \boxed{1705.6} \text{ cu.ft} - \boxed{380.0} \text{ cu.ft} = \boxed{2824.7} \text{ cu.ft}$$

Divide cu.ft by 27 cu.ft/cu.yd to calculate cubic yards: $\boxed{2824.7} \text{ cu.ft} \div 27 = \boxed{104.6} \text{ cu.yd}$

Add 30% for constructability: $\boxed{104.6} \text{ cu.yd} \times 1.3 = \boxed{136.0} \text{ cu.yd}$

D. Calculate Topsoil Material Volume: Total Mound Width X Total Mound Length X .5 ft

$$\boxed{45.7} \text{ ft} \times \boxed{70.4} \text{ ft} \times 0.5 \text{ ft} = \boxed{1609.9} \text{ cu.ft}$$

Divide cu.ft by 27 cu.ft/cu.yd to calculate cubic yards: $\boxed{1609.9} \text{ cu.ft} \div 27 = \boxed{59.6} \text{ cu.yd}$

Add 30% for constructability: $\boxed{59.6} \text{ cu.yd} \times 1.3 = \boxed{77.5} \text{ cu.yd}$




Pressure Distribution Design Worksheet



Project ID:

v 03.15.2023


- Media Bed Width: ft
- Minimum Number of Laterals in system/zone = Rounded up number of $[(\text{Media Bed Width} - 4) \div 3] + 1$.
 $[(\text{10} - 4) \div 3] + 1 = \boxed{3}$ laterals *Does not apply to at-grades*
- Designer Selected Number of Laterals: laterals *Cannot be less than line 2 (Except in at-grades)*
- Select Perforation Spacing: ft
- Select Perforation Diameter Size: in
- Length of Laterals = Media Bed Length(1.) - 2 Feet.
 $38.0 - 2\text{ft} = \boxed{36.0}$ ft *Perforation can not be closer than 1 foot from edge.*



- Determine the Number of Perforation Spaces. Divide the Length of Laterals(6.) by the Perforation Spacing(4.) and round down to the nearest whole number.
 $\text{Number of Perforation Spaces} = \boxed{36.0} \text{ ft} \div \boxed{3.0} \text{ ft} = \boxed{12} \text{ Spaces}$
- Number of Perforations per Lateral is equal to 1.0 plus the Number of Perforation Spaces(7.). Check table below to verify the number of perforations per lateral guarantees less than a 10% discharge variation. The value is double with a center manifold.

$$\text{Perforations Per Lateral} = \boxed{12} \text{ Spaces} + 1 = \boxed{13} \text{ Perfs. Per Lateral}$$

Maximum Number of Perforations Per Lateral to Guarantee <10% Discharge Variation											
1/4 Inch Perforations						7/32 Inch Perforations					
Perforation Spacing (Feet)	Pipe Diameter (Inches)					Perforation Spacing (Feet)	Pipe Diameter (Inches)				
	1	1 1/4	1 1/2	2	3		1	1 1/4	1 1/2	2	3
2	10	13	18	30	60	2	11	16	21	34	68
2 1/2	8	12	16	28	54	2 1/2	10	14	20	32	64
3	8	12	16	25	52	3	9	14	19	30	60
3/16 Inch Perforations						1/8 Inch Perforations					
Perforation Spacing (Feet)	Pipe Diameter (Inches)					Perforation Spacing (Feet)	Pipe Diameter (Inches)				
	1	1 1/4	1 1/2	2	3		1	1 1/4	1 1/2	2	3
2	12	18	26	46	87	2	21	33	44	74	149
2 1/2	12	17	24	40	80	2 1/2	20	30	41	69	135
3	12	16	22	37	75	3	20	29	38	64	128



END Connection

CENTER Connection

Perf Per Lateral:

Perf Per Lateral Equal Split:

OPTIONAL Perf Per Lateral Non-Equal Split*:

* must not exceed maximum number perfs per lateral in table

- Total Number of Perforations equals the Number of Perforations per Lateral (8.) multiplied by the Number of Perforated Laterals.(3.)

$$13 \text{ Perf. Per Lat.} \times \boxed{3} \text{ Number of Perf. Lat.} = \boxed{39} \text{ Total Number of Perf.}$$

- Spacing of laterals; Must be greater than 1 foot and no more than 3 feet: ft

- Select Type of Manifold Connection (End or Center):

If Center Manifold Connection the max number of perfs per lateral in the table can be doubled.

- Select Lateral Diameter (See Table): in

Pressure Distribution
Design Worksheet

13. Calculate the Square Feet per Perforation.

Recommended value is 4-11 ft² per perforation, Does not apply to At-Grades

a. Bed Area = Bed Width (ft) X Bed Length (ft)

$$10 \text{ ft} \times 38 \text{ ft} = 380 \text{ sq.ft}$$

b. Square Foot per Perforation = Bed Area ÷ by the Total Number of Perfs

$$380 \text{ sqft} \div 39 \text{ perf} = 9.7 \text{ sq.ft/perf}$$

14. Select Minimum Average Head: 1.0 ft

15. Select Perforation Discharge based on Table: 0.74 GPM per Perf

16. Flow Rate = Total Number of Perfs(9.) X Perforation Discharge(15.)

$$39 \text{ Perfs} \times 0.74 \text{ GPM per Perforation} = 29 \text{ GPM}$$

17. Volume of Liquid Per Foot of Distribution Piping (Table II): 0.110 Gallons/ft

18. Volume of Distribution Piping = Number of Perforated Laterals(3.) X Length of Laterals(6.) X Volume of Liquid Per Foot of Distribution Piping (17.)

$$3 \text{ ft} \times 36 \text{ ft} \times 0.110 \text{ gal/ft} = 11.9 \text{ Gallons}$$

19. Minimum Delivered Volume = Volume of Distribution Piping X 4

$$11.9 \text{ gals} \times 4 = 47.5 \text{ Gallons}$$

20. Maximum Delivered Volume = Design flow x 25%

$$450.0 \text{ gpd} \times 25\% = 112.5 \text{ Gallons}$$

21. Minimum Delivered vs Maximum Delivered evaluation: Volume ratio correct

Comments/Special Design Considerations:

Head (ft)	Perforation Discharge (GPM)			
	1/8	3/16	7/32	1/4
1.0 ^a	0.18	0.41	0.56	0.74
1.5	0.22	0.51	0.69	0.9
2.0 ^b	0.26	0.59	0.80	1.04
2.5	0.29	0.65	0.89	1.17
3.0	0.32	0.72	0.98	1.28
4.0	0.37	0.83	1.13	1.47
5.0 ^c	0.41	0.93	1.26	1.65
1 foot	Dwellings with 3/16 inch to 1/4 inch perforation			
2 feet	Dwellings with 1/8 inch perforations			
5 feet	Other establishments and MSTS with 3/16 inch to 1/4 inch perforations			
	Other establishments and MSTS with 1/8 inch perforations			

Table II Volume of Liquid in Pipe	
Pipe Diameter (inches)	Liquid Per Foot (Gallons)
1	0.045
1.25	0.078
1.5	0.110
2	0.170
3	0.380
4	0.661



Basic STA Pump Selection Design Worksheet



1. PUMP CAPACITY

Project ID:

v 03.15.2023

Pumping to Gravity or Pressure Distribution: Pressure

A. If pumping to gravity enter the gallon per minute of the pump: GPM (10 - 45 gpm)

B. If pumping to a pressurized distribution system: 29.0 GPM

C. Enter pump description: Demand Dosing


2. HEAD REQUIREMENTS

A. Elevation Difference 9 ft between pump and point of discharge:

B. Distribution Head Loss: 5 ft

C. Additional Head Loss*: ft (due to special equipment, etc.)

* Common additional head loss: gate valve = 1 ft each, globe valve = 1.5 ft each, splitter valve = see manufacturers details



Distribution Head Loss

Gravity Distribution = 0ft

Pressure Distribution based on Minimum Average Head Value on Pressure Distribution Worksheet:

Minimum Average Head	Distribution Head Loss
1ft	5ft
2ft	6ft
5ft	10ft

D. 1. Supply Pipe Diameter: 2.0 in

2. Supply Pipe Length: 27 ft

E. Friction Loss in Plastic Pipe per 100ft from Table I:

Friction Loss = 2.23 ft per 100ft of pipe

F. Determine Equivalent Pipe Length from pump discharge to soil dispersal area discharge point. Estimate by adding 25% to supply pipe length for fitting loss. Supply Pipe Length X 1.25 = Equivalent Pipe Length.

$$27 \text{ ft} \times 1.25 = 33.8 \text{ ft}$$

Table I. Friction Loss in Plastic Pipe per 100ft

Flow Rate (GPM)	Pipe Diameter (inches)			
	1	1.25	1.5	2
10	9.1	3.1	1.3	0.3
12	12.8	4.3	1.8	0.4
14	17.0	5.7	2.4	0.6
16	21.8	7.3	3.0	0.7
18		9.1	3.8	0.9
20		11.1	4.6	1.1
25		16.8	6.9	1.7
30		23.5	9.7	2.4
35			12.9	3.2
40			16.5	4.1
45			20.5	5.0
50				6.1
55				7.3
60				8.6
65				10.0
70				11.4
75				13.0
85				16.4
95				20.1

G. Calculate Supply Friction Loss by multiplying Friction Loss Per 100ft(E.) by the Equivalent Pipe Length(F.) and divide by 100.

Supply Friction Loss =

$$2.23 \text{ ft per 100ft} \times 33.8 \text{ ft} + 100 = 0.8 \text{ ft}$$

H. Total Head requirement is the sum of the Elevation Difference(2A) + Distribution Head Loss(2B) + Additional Head Loss(2C) + Supply Friction Loss(2G)

$$9.0 \text{ ft} + 5.0 \text{ ft} + \text{ } \text{ ft} + 0.8 \text{ ft} = 14.8 \text{ ft}$$

3. PUMP SELECTION

A pump must be selected to deliver at least **29.0** GPM with at least **14.8** feet of total head.

Comments:

Gould PE31 produces 38GPM at 14.8TFH



STA Dosing Pump Tank Design Worksheet (Demand Dose)

MINNESOTA POLLUTION CONTROL AGENCY

DETERMINE TANK CAPACITY AND DIMENSIONS

Project ID:

v 03.15.2023

1. A. Design Flow (Design Sum. 1A):	450	GPD	C. Tank Use:	Dosing	
B. Min. required pump tank capacity:	500	Gal	D. Recommended pump tank capacity:	500	Gal
2. A. Tank Manufacturer:	Existing		B. Tank Model:		
C. Capacity from manufacturer:	500	Gallons	<p><i>Note: Design calculations are based on this specific tank. Substituting a different tank model will change the pump float or timer settings. Contact designer if changes are necessary.</i></p>		
D. Gallons per inch from manufacturer:	12.0	Gallons per inch			
E. Liquid depth of tank from manufacturer:	43.0	inches			

DETERMINE DOSING VOLUME

3. Calculate Volume to Cover Pump (The inlet of the pump must be at least 4-inches from the bottom of the pump tank & 2 inches of water covering the pump is recommended)

(Pump and block height + 2 inches) X Gallons Per Inch (2D)

$$(\boxed{16} \text{ in} + 2 \text{ inches}) \times \boxed{12.0} \text{ Gallons Per Inch} = \boxed{216} \text{ Gallons}$$

4. Minimum Delivered Volume = 4 X Volume of Distribution Piping:

$$-Item 19 of the Pressure Distribution STA or Item 11 of Non-level STA \quad \boxed{48} \text{ Gallons (Minimum dose)} \quad \boxed{4.0} \text{ inches/dose}$$

5. Calculate Maximum Pumpout Volume (25% of Design Flow(1A))

$$\text{Design Flow: } \boxed{450} \text{ GPD} \times 0.25 = \boxed{113} \text{ Gallons (Maximum dose)} \quad \boxed{9.4} \text{ inches/dose}$$

6. Select a pumpout volume that meets both Minimum and Maximum: 80 Gallons

7. Calculate Doses Per Day = Design Flow(1A) ÷ Delivered Volume(6.)

$$\boxed{450} \text{ gpd} \div \boxed{80} \text{ gal} = \boxed{5.63} \text{ Doses*}$$

* Doses need to be equal to or greater than 4

8. Calculate Drainback:

$$A. \text{ Diameter of Supply Pipe: } \boxed{2} \text{ inches}$$

$$B. \text{ Length of Supply Pipe: } \boxed{27} \text{ feet}$$

$$C. \text{ Volume of Liquid Per Lineal Foot of Pipe: } \boxed{0.170} \text{ Gallons/ft}$$

$$D. \text{ Drainback = Length of Supply Pipe(8B) X Volume of Liquid Per Lineal Foot of Pipe(8C)}$$

$$\boxed{27} \text{ ft} \times \boxed{0.170} \text{ gal/ft} = \boxed{4.6} \text{ Gallons}$$

9. Total Dosing Volume = Delivered Volume(6.) + Drainback (8D)

$$\boxed{80} \text{ gal} + \boxed{4.6} \text{ gal} = \boxed{85} \text{ Gallons}$$

Volume of Liquid in Pipe

Pipe Diameter (inches)	Liquid Per Foot (Gallons)
1	0.045
1.25	0.078
1.5	0.110
2	0.170
3	0.380
4	0.661

10. Minimum Alarm Volume = Depth of alarm (2 or 3 inches) X gallons per inch of tank(2D)

$$\boxed{3} \text{ in} \times \boxed{12.0} \text{ gal/in} = \boxed{36.0} \text{ Gallons}$$

11. Reserve Capacity Volume = [Tank Liquid Depth(2E) - Alarm Float Depth(10.)] x gallons per inch of tank(2D)

$$[\boxed{43.0} \text{ in} - \boxed{28.0} \text{ in}] \times \boxed{12.0} \text{ gal/in} = \boxed{179.4} \text{ Gallons}$$

DEMAND DOSE FLOAT SETTINGS

Alarm and Pump are to be wired on separate circuits and inspected by the electrical inspector

12. Calculate Float Separation Distance using Dosing Volume.

Total Dosing Volume(9.) ÷ Gallons Per Inch(2D)

$$\boxed{85} \text{ gal} \div \boxed{12.0} \text{ gal/in} = \boxed{7.0} \text{ inches}$$

13. Measuring from bottom of tank:

A. Distance to set Pump Off Float = Pump + block height + 2 inches


$$\boxed{16} \text{ in} + 2 \text{ in} = \boxed{18} \text{ inches}$$

B. Distance to set Pump On Float = Distance to Set Pump-Off Float(13A) + Float Separation Distance(12.)

$$\boxed{18} \text{ in} + \boxed{7.0} \text{ in} = \boxed{25} \text{ inches}$$

C. Distance to set Alarm Float = Distance to set Pump-On Float(13B) + Alarm Depth (2-3 inches)(10.)

$$\boxed{25} \text{ in} + \boxed{3.0} \text{ in} = \boxed{28} \text{ inches}$$



Doug and Lauri Askelson
17170 220th st
140148000

Reusing existing 1500-2, update with risers on septic compartment, event counter required.

2" supply line


12" sand lift from highest elevation

26'x40' soil absorption area


10'x38' rock bed, 9" rock depth minimum

Three 1-1/2" laterals, 1/4" perfs spaced 36"

Electric fence to be routed around soil treatment area to protect from livestock



Soil Map—Becker County, Minnesota



8/16/2024
Page 1 of 3

Web Soil Survey
National Cooperative Soil Survey

Map Scale: 1:1,200 if printed on A landscape (11" x 8.5" sheet).
Map projection: Web Mercator
Corner coordinates: WGS84
Edge ticks: UTM Zone 14N WGS
Meters
90
300
Feet
15 30 60
50 100 200
1 15 30 60

କୁଳାଳରେ ଶୁଣୁଥିବା କାହାର କାହାର କାହାର କାହାର କାହାର

Map projection: Web Mercator Corner coordinates: WGS84 Edge tiles: UTM Zone 14N WGS84

z

Natural Resources
Conservation Service

Web Soil Survey
National Cooperative Soil Survey

8/16/2024
Page 1 of 3



MAP LEGEND

Area of Interest (AOI)	Area of Interest (AOI)		Spoil Area			
Soils			Stony Spot			
	Soil Map Unit Polygons		Very Stony Spot			
	Soil Map Unit Lines		Wet Spot			
	Soil Map Unit Points		Other			
Special Point Features			Special Line Features			
	Blowout		Water Features			
	Borrow Pit		Streams and Canals			
	Clay Spot		Transportation			
	Closed Depression		Rails			
	Gravel Pit		Interstate Highways			
	Gravelly Spot		US Routes			
	Landfill		Major Roads			
	Lava Flow		Local Roads			
			Background			
				Aerial Photography		
					Mine or Quarry	
					Miscellaneous Water	
					Perennial Water	
					Rock Outcrop	
					Saline Spot	
					Sandy Spot	
					Severely Eroded Spot	
					Sinkhole	
					Slide or Slip	
					Sodic Spot	

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:20,000.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service

Web Soil Survey URL:

Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Becker County, Minnesota
Survey Area Data: Version 19, Sep 9, 2023

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: May 24, 2021—Jun 12, 2021

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Map Unit Legend

Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
J118C	Hokans-Svea-Buse complex, 2 to 12 percent slopes	4.0	61.7%
J119D	Barnes-Svea-Buse complex, 3 to 15 percent slopes	2.5	38.3%
Totals for Area of Interest		6.6	100.0%

Becker County, Minnesota

J119D—Barnes-Svea-Buse complex, 3 to 15 percent slopes

Map Unit Setting

National map unit symbol: 2yw63
Elevation: 920 to 2,130 feet
Mean annual precipitation: 22 to 31 inches
Mean annual air temperature: 37 to 46 degrees F
Frost-free period: 120 to 160 days
Farmland classification: All areas are prime farmland

Map Unit Composition

Barnes and similar soils: 35 percent
Svea and similar soils: 30 percent
Buse and similar soils: 25 percent
Minor components: 10 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Barnes

Setting

Landform: Ground moraines
Landform position (two-dimensional): Backslope
Landform position (three-dimensional): Side slope
Down-slope shape: Linear
Across-slope shape: Linear
Parent material: Fine-loamy till

Typical profile

Ap - 0 to 8 inches: clay loam
Bw - 8 to 17 inches: clay loam
Bk - 17 to 45 inches: clay loam
C - 45 to 79 inches: clay loam

Properties and qualities

Slope: 3 to 13 percent
Depth to restrictive feature: More than 80 inches
Drainage class: Well drained
Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high (0.20 to 2.00 in/hr)
Depth to water table: About 59 to 75 inches
Frequency of flooding: None
Frequency of ponding: None
Calcium carbonate, maximum content: 40 percent
Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)
Available water supply, 0 to 60 inches: High (about 10.0 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 3e
Hydrologic Soil Group: C
Ecological site: R102AY010SD - Loamy
Forage suitability group: Loam (G102AY100SD)
Other vegetative classification: Loam (G102AY100SD)
Hydric soil rating: No

Description of Svea

Setting

Landform: Ground moraines
Landform position (two-dimensional): Footslope
Landform position (three-dimensional): Base slope
Down-slope shape: Concave
Across-slope shape: Linear
Parent material: Fine-loamy till

Typical profile

Ap - 0 to 7 inches: silty clay loam
A - 7 to 17 inches: silty clay loam
Bw - 17 to 26 inches: clay loam
Bk - 26 to 49 inches: clay loam
C - 49 to 79 inches: clay loam

Properties and qualities

Slope: 3 to 12 percent
Depth to restrictive feature: More than 80 inches
Drainage class: Moderately well drained
Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high (0.20 to 2.00 in/hr)
Depth to water table: About 30 to 39 inches
Frequency of flooding: None
Frequency of ponding: None
Calcium carbonate, maximum content: 40 percent
Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)
Available water supply, 0 to 60 inches: High (about 10.5 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 2e
Hydrologic Soil Group: C
Ecological site: R102AY010SD - Loamy
Forage suitability group: Loam (G102AY100SD)
Other vegetative classification: Loam (G102AY100SD)
Hydric soil rating: No

Description of Buse

Setting

Landform: Ground moraines
Landform position (two-dimensional): Shoulder, backslope, summit
Landform position (three-dimensional): Nose slope
Down-slope shape: Convex

Across-slope shape: Linear
Parent material: Fine-loamy till

Typical profile

Ap - 0 to 8 inches: clay loam
Bk - 8 to 31 inches: clay loam
C - 31 to 79 inches: clay loam

Properties and qualities

Slope: 5 to 15 percent
Depth to restrictive feature: More than 80 inches
Drainage class: Well drained
Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high (0.20 to 2.00 in/hr)
Depth to water table: About 59 to 75 inches
Frequency of flooding: None
Frequency of ponding: None
Calcium carbonate, maximum content: 40 percent
Maximum salinity: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)
Available water supply, 0 to 60 inches: High (about 9.7 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 4e
Hydrologic Soil Group: C
Ecological site: R102AY012SD - Thin Upland
Forage suitability group: Loam (G102AY100SD)
Other vegetative classification: Loam (G102AY100SD)
Hydric soil rating: No

Minor Components

Lakepark

Percent of map unit: 5 percent
Landform: Drainageways on ground moraines
Landform position (two-dimensional): Toeslope
Down-slope shape: Concave
Across-slope shape: Linear
Ecological site: R102AY002SD - Linear Meadow
Other vegetative classification: Wet (G102AY900SD)
Hydric soil rating: Yes

Formdale

Percent of map unit: 5 percent
Landform: Ground moraines
Landform position (two-dimensional): Footslope
Landform position (three-dimensional): Side slope
Down-slope shape: Linear
Across-slope shape: Linear
Ecological site: R102AY010SD - Loamy
Other vegetative classification: Loam (G102AY100SD)

Hydric soil rating: No

Data Source Information

Soil Survey Area: Becker County, Minnesota
Survey Area Data: Version 19, Sep 9, 2023





140148000-2024



520 Lafayette Road North
St. Paul, MN 55155-4194

Compliance inspection report form

Existing Subsurface Sewage Treatment System (SSTS)

Doc Type: Compliance and Enforcement

Instructions: Inspector must submit completed form to Local Governmental Unit (LGU) and system owner within 15 days of final determination of compliance or noncompliance. Instructions for filling out this form are located on the Minnesota Pollution Control Agency (MPCA) website at <https://www.pca.state.mn.us/sites/default/files/wq-wwsts4-31a.pdf>.

Property information

Parcel ID# or Sec/Twp/Range: <u>140148000</u>	Reason for Inspection	Local tracking number: <u>Sale</u>
Local regulatory authority info: <u>Becker County</u>		
Property address: <u>17170 220th St. Audubon, MN 56511</u>		
Owner/representative: <u>Lauri Askelson</u>	Owner's phone: <u>701-200-6082</u>	
Brief system description: 1500/2 comp. tank with lift pump to chamber trench drainfield. 1000 sq.ft.		

System status

System status on date (mm/dd/yyyy): 6/26/2024

Compliant – Certificate of compliance*

(Valid for 3 years from report date unless evidence of an imminent threat to public health or safety requiring removal and abatement under section 145A.04, subdivision 8 is discovered or a shorter time frame exists in Local Ordinance.)

*Note: Compliance Indicates conformance with Minn. R. 7080.1500 as of system status date above and does not guarantee future performance.

Noncompliant – Notice of noncompliance

Systems failing to protect ground water must be upgraded, replaced, or use discontinued within the time required by local ordinance.

An imminent threat to public health and safety (ITPHS) must be upgraded, replaced, or its use discontinued within ten months of receipt of this notice or within a shorter period if required by local ordinance or under section 145A.04 subdivision 8.

Reason(s) for noncompliance (check all applicable)

- Impact on public health (Compliance component #1) – *Imminent threat to public health and safety*
- Tank integrity (Compliance component #2) – *Failing to protect groundwater*
- Other Compliance Conditions (Compliance component #3) – *Imminent threat to public health and safety*
- Other Compliance Conditions (Compliance component #3) – *Failing to protect groundwater*
- System not abandoned according to Minn. R. 7080.2500 (Compliance component #3) – *Failing to protect groundwater*
- Soil separation (Compliance component #5) – *Failing to protect groundwater*
- Operating permit/monitoring plan requirements (Compliance component #4) – *Noncompliant - local ordinance applies*

Comments or recommendations

Tank is in compliance, drainfield does not make soil separation requirements. New drainfield needed.

Certification

I hereby certify that all the necessary information has been gathered to determine the compliance status of this system. No determination of future system performance has been nor can be made due to unknown conditions during system construction, possible abuse of the system, inadequate maintenance, or future water usage.

By typing my name below, I certify the above statements to be true and correct, to the best of my knowledge, and that this information can be used for the purpose of processing this form.

Business name: Stoll Inspections Inc.

Certification number: 7526

Inspector signature: Phil Stoll

License number: 2982

(This document has been electronically signed)

Phone: 218-839-1849

Necessary or locally required supporting documentation (must be attached)

- Soil observation logs
- System/As-Built
- Locally required forms
- Tank Integrity Assessment
- Operating Permit
- Other Information (list):

Property Address: 17170 220th St. Audubon, MN 56511

Business Name: Stoll Inspections Inc.

Date: 6/26/2024

1. Impact on public health – Compliance component #1 of 5

Compliance criteria:

System discharges sewage to the ground surface	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
System discharges sewage to drain tile or surface waters.	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
System causes sewage backup into dwelling or establishment.	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No

Any "yes" answer above indicates the system is an imminent threat to public health and safety.

Attached supporting documentation:

Other: _____

Not applicable

Describe verification methods and results:

2. Tank integrity – Compliance component #2 of 5

Compliance criteria:

System consists of a seepage pit, cesspool, drywell, leaching pit, or other pit?	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Sewage tank(s) leak below their designed operating depth?	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
If yes, which sewage tank(s) leaks:	

Any "yes" answer above indicates the system is failing to protect groundwater.

Attached supporting documentation:

Empty tank(s) viewed by inspector

Name of maintenance business: Deweys

License number of maintenance business: L2884

Date of maintenance: 6/25/2024

Existing tank integrity assessment (Attach)

Date of maintenance (mm/dd/yyyy): _____ (must be within three years)

(See form instructions to ensure assessment complies with Minn. R. 7082.0700 subp. 4 B (1))

Tank is Noncompliant (pumping not necessary – explain below)

Other: _____

Describe verification methods and results:

Property Address: 17170 220th St. Audubon, MN 56511

Business Name: Stoll Inspections Inc.

Date: 6/26/2024

3. Other compliance conditions – Compliance component #3 of 5

3a. Maintenance hole covers appear to be structurally unsound (damaged, cracked, etc.), or unsecured?

Yes No Unknown

3b. Other issues (electrical hazards, etc.) to immediately and adversely impact public health or safety? Yes No Unknown

**Yes to 3a or 3b - System is an imminent threat to public health and safety.*

3c. System is non-protective of ground water for other conditions as determined by inspector? Yes No

3d. System not abandoned in accordance with Minn. R. 7080.2500? Yes No

**Yes to 3c or 3d - System is failing to protect groundwater*

Describe verification methods and results:

Attached supporting documentation: Not applicable

4. Operating permit and nitrogen BMP* – Compliance component #4 of 5 Not applicable

Is the system operated under an Operating Permit? Yes No If "yes", A below is required

Is the system required to employ a Nitrogen BMP specified in the system design? Yes No If "yes", B below is required

BMP = Best Management Practice(s) specified in the system design

If the answer to both questions is "no", this section does not need to be completed.

Compliance criteria:

a. Have the operating permit requirements been met? Yes No

b. Is the required nitrogen BMP in place and properly functioning? Yes No

Any "no" answer indicates noncompliance.

Describe verification methods and results:

Attached supporting documentation: Operating permit (Attach)

5. Soil separation – Compliance component #5 of 5

Date of installation 7/30/2008 Unknown
(mm/dd/yyyy)

Shoreland/Wellhead protection/Food
beverage lodging? Yes No

Attached supporting documentation:

Soil observation logs completed for the report

Two previous verifications of required vertical separation

Not applicable (No soil treatment area)

Compliance criteria (select one):

5a. For systems built prior to April 1, 1996, and
not located in Shoreland or Wellhead
Protection Area or not serving a food,
beverage or lodging establishment: Yes No*

Drainfield has at least a two-foot vertical
separation distance from periodically
saturated soil or bedrock.

5b. Non-performance systems built
April 1, 1996, or later or for non-
performance systems located in Shoreland
or Wellhead Protection Areas or serving a
food, beverage, or lodging establishment: Yes No*

Drainfield has a three-foot vertical
separation distance from periodically
saturated soil or bedrock.*

5c. "Experimental", "Other", or "Performance"
systems built under pre-2008 Rules;
Type IV or V systems built under 2008
Rules 7080.2350 or 7080.2400
(Intermediate Inspector License required \leq
2,500 gallons per day; Advanced Inspector
License required $>$ 2,500 gallons per day)

Drainfield meets the designed vertical
separation distance from periodically
saturated soil or bedrock.

*Any "no" answer above indicates the system is
failing to protect groundwater.

Describe verification methods and results:

Indicate depths or elevations


A. Bottom of distribution media 30"

B. Periodically saturated soil/bedrock 40"

C. System separation 10"

D. Required compliance separation* 36"

*May be reduced up to 15 percent if allowed by Local
Ordinance.




Upgrade requirements: (Minn. Stat. § 115.55) An imminent threat to public health and safety (ITPHS) must be upgraded, replaced, or its use discontinued within ten months of receipt of this notice or within a shorter period if required by local ordinance. If the system is failing to protect ground water, the system must be upgraded, replaced, or its use discontinued within the time required by local ordinance. If an existing system is not failing as defined in law, and has at least two feet of design soil separation, then the system need not be upgraded, repaired, replaced, or its use discontinued, notwithstanding any local ordinance that is more strict. This provision does not apply to systems in shoreland areas, Wellhead Protection Areas, or those used in connection with food, beverage, and lodging establishments as defined in law.

Parcel Number: 140148000
Date & Initial: 6-26-24 PJS

System Drawing

The system drawing which includes and identifies a graphic scale in feet or indicates all setback distances, all septic/holding/lift tanks, drainfields, wells within 100 feet of system (indicate depth of wells), dwelling and non-dwelling structures, lot lines, road right-of-ways, easements, OHVLe, wetlands, and topographic features (i.e. bluffs).



Additional Comments: Septic is non-compliant